

FUEL BOX

SELF BUNDED TANK RANG



**CONTROL
INTEGRATE
GENERATE**

SUITABLE FOR THE STORAGE & DISPENSING OF DIESEL, KEROSENE, LUBRICANTS, PETROL & WASTE OIL

- The Fuel Box is a market leading self banded tank, with versatile under-hatch connections and an intelligent design certified for lifting when full (Up to 6600L).
- Unique tank in tank design approved to UL142 / ULCS601 / AS1940, AS1692, AS1170, AS4100, AS1554.1 /BS799 /PPG2.
- Certified Crane Lifting Points (Up to and including 6600L)
- Removable manway for ease of maintenance.
- The outer tank will hold 110% of the inner tank's capacity.
- UN31A/Y approved for the transport of Dangerous Goods by Road, Rail and Sea, Packaging Groups II & III (660L to 3300L).
- Lockable hatch lid with access for hoses, under hatch sockets and suction spears can operate with the hatch closed.
- Additional 50mm (2") hose entry and exit sockets on top of tank.
- Secure under-hatch generator hose suction and return points, to accommodate up to 3 generators.
- 4 x way forklift pockets.
- Incremental dipstick.
- Stackable - 3-high empty and 2-high when full.
- Supplied with all required statutory decals.
- Movable when full.



PRODUCT RANGE

	BOX 0.6	BOX 1.1	BOX 2.25	BOX 3.3	BOX 5.5	BOX 6.6	BOX 8.8	BOX 11
Capacity	600L	1100L	2250L	3300L	5500L	6600L	8800L	11000L
Safe Fill Level	550L	1000L	2000L	3000L	5000L	6000L	8000L	10000L
Length (mm)	1086	1374	2294	2294	2496	2966	3916	4876
Width (mm)	724	1086	1086	1546	2294	2294	2294	2294
Height (mm)	1270	1270	1270	1270	1270	1270	1270	1270
Tare Weight (kg)	451	594	885	1096	1530	1809	2170	2689

COMES WITH

- 1 x 25mm (1") Suction Spear
- 2 x 13mm (1/2") Suction Spear
- 3 x 40mm (1 1/2") Return Point
- 1 x Spare 80mm (3") Socket
- 4 x Spare 50mm (2") Socket Top of Tank
- 50mm (2") Fill Point - Splash Fill Only
- 1 x 50mm (2") Overfill Valve
- Incremented Dip Stick (Select Models)
- Statutory Signage
- 4 Way Forklift Pockets
- Certified Lift Full Crane Lugs on Each Corner
- Finish Painted White Marine Specification